


shieldex



Shieldex® VELCRO® Hook & Loop + C12

Hook: 11000011625C12/11000013026C12/11000015026C12

Loop: 11000011626C12/11000013025C12/11000015025C12

Material	Polyamide
Metal Plated	99.9 % Pure Silver
Width	16/25/30/50 mm
Weight	Average 4/9/17 g/m
Cycle life	Average 500 cycles
Coating	C12
Surface Resistivity	< 1.3 Ω/□ (Hook & Loop closed)
Make Up	25 m on roll
Storage and Handling	According to our care and handling instructions
Compliance and Certification	DIN EN ISO 9001:2015, REACH, RoHS

Alterations Reserved 30.01.24/02 – The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note our handling and storage instructions as well accessible at www.shieldex.de.

Physical Adress
V Technical Textiles, Inc
320 South Main Street
Newark, NY 14513

Mailing Adress
V Technical Textiles, Inc
4502 State Rt. 31
Palmyra, NY 14522

Contact
Phone: (315)-597-1674
Fax: (315)-597-6687
info@vtechtextiles.com

