

Ag	Cu	Ni	Sn
----	----	----	----

Shieldex® Silverjersey Modal Black

8001602007



Raw Material	Jersey construction: fine rib bonded (CMD 83 % /PA 17 % with 99.9 % pure Silver)
Colour	Black
Yarn Count Silvered Yarn	About 54/10 dtex
Measured Frequency	0.2 GHz – 5 GHz
Shielding Effectiveness	Up to 20 dB
Total Weight	165 g/m ² ± 10 %
Total Thickness	0.71 mm ± 10 %
Roll Width	165 ± 5 cm
Roll Length	60 m and less
Temperature Range	-30 °C to 90 °C
Storage and Handling	According to our care and handling instructions
Compliance and Certification	DIN EN ISO 9001:2015, REACH, RoHS

Alterations Reserved 28.06.2019/03 – The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note our handling and storage instructions as well accessible at www.shieldex.de.

Physical Address
V Technical Textiles, Inc
320 South Main Street
Newark, NY 14513

Mailing Address
V Technical Textiles, Inc
4502 State Rt. 31
Palmyra, NY 14522

Contact
Phone: (315)-597-1674
Fax: (315)-597-6687
info@vtechtextiles.com

