

shieldex

Ag Cu Ni Sn

Shieldex® 22/1 + 113/32 PES

261151022113



Material	22/1 dtex Polyamide / Nylon 6 + 113/32 dtex Polyester
Metal Plated	99.9 % Pure Silver
Yarn count of Twist	142 ± 3 dtex
Twist	Z 300 ± 10 %
Electrical Resistivity	< 200 Ω/cm
Yield	68.000 m/kg ± 3 %
Tenacity	58 ± 4 cN/tex
Elongation / Break	17 % ± 3
Make Up	On cones 230 mm 3° 30
Packaging	Average 800 g net yarn per cone 12 or 24 cones per carton
Storage and Handling	According to our care and handling instructions
Compliance and Certification	OEKO-TEX® Standard 100, DIN EN ISO 9001:2015, REACH, RoHS

Alterations Reserved 11.10.21/07 — The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note our handling and storage instructions as well accessible at www.shieldex.de.

Physical Adress
V Technical Textiles, Inc
320 South Main Street
Newark, NY 14513

Mailing Adress
V Technical Textiles, Inc
4502 State Rt. 31
Palmyra, NY 14522

Contact
Phone: (315)-597-1674
Fax: (315)-597-6687
info@vtechtextiles.com


V Technical Textiles Inc.

