

Ag	Cu	Ni	Sn
----	----	----	----

## Shieldex<sup>®</sup> 180 $\mu$ Monofil - preliminary

2002120180



<b>Material</b>	Polyamide / Nylon 6
<b>Metal Plated</b>	99.9 % Pure Silver
<b>Yarn count raw</b>	290 dtex $\pm$ 10 dtex
<b>Yarn count silverized</b>	310 dtex $\pm$ 10 dtex
<b>Yield</b>	32.200 m/kg $\pm$ 4 %
<b>Tenacity</b>	5.5 cN/dtex $\pm$ 0.5
<b>Elongation / Break</b>	28 % $\pm$ 5
<b>Resistivity</b>	< 2 k $\Omega$ /m
<b>Make Up</b>	On cones 230 mm 3° 30
<b>Packaging</b>	1 lbs (454g) net yarn per cone 12 or 24 cones per carton
<b>Storage and Handling</b>	According to our care and handling instructions
<b>Compliance and Certification</b>	DIN EN ISO 9001:2015, REACH, RoHS

**Alterations Reserved 28.02.17/02** – The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note our handling and storage instructions as well accessible at [www.shieldex.de](http://www.shieldex.de).

**Physical Address**  
V Technical Textiles, Inc  
320 South Main Street  
Newark, NY 14513

**Mailing Address**  
V Technical Textiles, Inc  
4502 State Rt. 31  
Palmyra, NY 14522

**Contact**  
Phone: (315)-597-1674  
Fax: (315)-597-6687  
[info@vtechtextiles.com](mailto:info@vtechtextiles.com)

